


360 BEND - FR010113

The 360° bend neon flexible delivers uniform all-around illumination with seamless light distribution. the 360° bending capability allows smooth curves and circular designs, making it ideal for creative lighting applications. Featuring a dust-resistant matte finish, it ensures a clean and consistent appearance. With an IP65 rating, it is suitable for indoor decorative and artistic use, supporting versatile installation methods for dynamic lighting designs.



DIMENSION



TECHNICAL PARAMETERS

Input Voltage	12V DC 24V DC
Wattage	10W/m
Lumens Output	518lm/m @ 3000K
Colour Temp.	2700K 3000K 4000K
CRI	>90
MacAdam Step	≤2 SDCM (binning consistency)
IP Rating	IP65 IP67
Operating Temp.	-20°C to +55°C
Reel Length	5m 10m
Cutting Pitch	25mm
Lifespan	>50,000 hrs
Dimmable	TRIAC 0-10V DALI
Material	Dow SILASTIC™ ET-7021

END CAPS & CABLE LEAD OPTIONS




Front Cable Entry




Closed end cap

ACCESSORIES



PC Profile



PC Clips

ORDERING CODE

ARC – FR010113 – 24V – 3000K – 90CRI – IP65 – 10M
 [Brand] – [Series] – [Voltage] – [CCT] – [CRI] – [IP Rating] – [Length]